

## OAK TOUCH

### DATA SHEET

- Product:** Prefinished Two-Layer Parquet
- Essence:** Oak (*Quercus Petrae*)
- Processing:** bevelled, gently brushed, pigmented
- Finishing:** UV Oil
- Thickness:** mm 14
- Noble wood:** mm 4
- Width:** mm 140/190
- Length:** mm 800-2200 (max. 15% of the supply, planks may be shorter than mm 800)
- Gluing:** gluing of the noble layer to the birch substrate is carried out with D4 vinyl glues
- Joints:** micrometrical with tolerances of 0.1 mm; tongue-and-groove on all four sides
- Grooves:** transverse grooves in the substrate allow longitudinal flexibility of the plank
- Grading:** Top Class ( $\Delta$ ): straight, slanted and flat grain, flamed and curly; moderate presence of small and sound filled knots; colour variation permitted
- Laying:** Glued or floating
- Certifications:** Compliance with UNI-EN 14342:2013 on CE marking of the product and compliance with release of dangerous substances:



- Pentachlorophenol content: < 5ppm
- Formaldehyde emission: class E1
- Thermal conductivity: 0.17 W/mk
- Biological durability: class 3
- Fire reaction class Cfls1

#### More information

The product is suitable for laying on underfloor heating systems.  
The dimensions and surface development of the lists contained in each package are shown on the label.  
For installation of the product, please refer to the recommendation sheet.  
For cleaning and maintenance, we recommend using detergents and products specifically for parquet.  
Once the product has reached the end of its life cycle, it must be disposed of at authorised dumps.

## RECOMMENDATION

- 1) Store the product into a dry place with no temperature fluctuations. Some days before the installation the planks should be left in the room where they are about to be laid and given time to adjust.
- 2) Open the packaging carefully to avoid the damage of the planks. We recommend the disposal of packaging in accordance with current regulations.
- 3) Pay attention to sharp edges. Do not hit the planks to preserve the extreme precision of the joint system.
- 4) When laying the planks, we recommend the use of rubber-coated tools.
- 5) For a suitable installation, the screed must be dry, compact, smooth and without cracks and it may contain only 2.5% moisture at the very most. If these prerequisites are not met, do not proceed with laying the floor until proper adjustment treatments are carried out.
- 6) "Alberani Parketti" products should be preferably laid by glueing. Use only single or two-component polyurethane adhesives for glueing the planks.
- 7) Once the floor has been laid, humidity in the area has to be around 55% and the temperature kept at around 20-21°, to keep the structural features of the parquet.
- 8) Because of our strict quality control checks, our products are guaranteed if boxed: in the event of small defects, please report them promptly before the installation.